



## A19 7-WATT LED

### High Efficiency

- Only 7W
- An ideal replacement for 60W A19 incandescent
- 53W savings
- 440 lumens
- 63 lumens per watt

### Phenomenal Light Quality

- Color Rendering Index of  $\geq 82$
- Color Temperature of 2700K & 3000K



# LUMIVERSAL

*lighting the way to energy savings*

## Key Features & Benefits:

### Dimming Capable

- 100% to 10%

### Long Life Expectancy

- 30,000-hour life
- Up to 20x longer life than incandescent lamps
- Reduced re-lamping

### Suitable for wide range of applications

- Temperature Range: -25°C/13°F to 45°C/113°F

### Emits significantly less heat than halogen

### Safe

- Emits no UV/IR light
- Contains no mercury

### Applications:

- Commercial & Office Spaces
- Hotels
- Restaurants
- Retail
- Accent Display Lighting
- Recessed Down Lighting
- Track lighting
- Residential

### Designed in California

### Made in the United States

## Warranty:

2-Year, Full Replacement

## Total Lifetime Savings

	Existing Lamp Watts		
	60	75	100
\$0.08	\$38.21	\$44.78	\$55.73
\$0.10	\$44.02	\$52.23	\$65.92
\$0.12	\$49.82	\$59.68	\$76.10
\$0.14	\$55.62	\$67.12	\$86.28
\$0.16	\$61.43	\$74.57	\$96.47
\$0.18	\$67.23	\$82.01	\$106.65
\$0.20	\$73.04	\$89.46	\$116.84

Based on 12hrs/day, 365days/year, 9 months cooling and 25,000hr lamp life (Halogen lamp @ 1,500 hr life @ \$0.75 each)

## Annual Energy Savings

	Existing Lamp Watts		
	60	75	100
\$0.08	\$18.57	\$23.83	\$32.59
\$0.10	\$23.21	\$29.78	\$40.73
\$0.12	\$27.86	\$35.74	\$48.88
\$0.14	\$32.50	\$41.70	\$57.03
\$0.16	\$37.14	\$47.65	\$65.17
\$0.18	\$41.79	\$53.61	\$73.32
\$0.20	\$46.43	\$59.57	\$81.47

Based on 12hrs/day, 365 days/year

## Annual HVAC Savings

	Existing Lamp Watts		
	60	75	100
\$0.08	\$4.64	\$5.96	\$8.15
\$0.10	\$5.80	\$7.45	\$10.18
\$0.12	\$6.96	\$8.94	\$12.22
\$0.14	\$8.12	\$10.42	\$14.26
\$0.16	\$9.29	\$11.91	\$16.29
\$0.18	\$10.45	\$13.40	\$18.33
\$0.20	\$11.61	\$14.89	\$20.37

Based on 12hrs/day, 365 days/year and 9 months cooling

Model Number	Watts	Beam Angle	Base	Rated Average Life (Hrs)	Approx. Lumens	CRI	Color Temp.
LEDA19-120-830/7-U	7	120°	E26	30,000	440	80	3000K
LEDA19-120-827/7-U	7	120°	E26	30,000	380	80	2700K

In accordance with our policy to consistently improve our products, the specifications contained herein are subject to change without notice.

## Lumiversal, Inc.

1709-A Little Orchard Street  
San Jose, CA 95125 USA

Phone: (888) 788-8144  
Fax: (888) 788-8442

www.lumiversal.net  
info@lumiversal.net

## Technical Specifications:

Input Voltage: 120V AC/DC

Input Current: Max 0.125A

Input Frequency: 50/60Hz

